



## Mix Tank Specifications

Mixer: (4) 10 HP mixer with gearbox, electric motor, 40" dia bottom impeller, 20" mid lever impeller, 4 blades per impeller  
 controls: Front mounted service disconnect for power connection, top mounted motor control center for each motor with power light, motor run light, starts, stop, each motor equipped with circuit breaker and overload heater protection.

- Dimensions: Overall: 46' Long, 8' 6" wide, 11" high, 500bbl capacity
- Pick Up: Standard 5th wheel king pin
- Electrical: 440v, 3 phase, 80amp
- Relief Valve: Flange mount blaylock II10 p/v vent 16oz pressure
- Roof: 4" Flange with blind cap and chain mounted on top
- Front: Sump mounted 4" flanged drain valve, bull plug, chain
- Rear: 4" Flange valve, threaded flange, plug, chain remote operation handle
- Manways: (2) 38" Manways, (2) 21 1/2 id, domed lid
- Hand Rails: Access stairs, safety walk way on roof, folding hand rails
- Wheels: 11.00 X 22.5 Tubless tire on 10 hole steel wheel
- Structure: 25k axle, automatic slack adjusters, top mounted, 30 service chambers, on board drums, hutch 9700 suspension, 3 leaf high arch springs
- Lights: DOT tail lights and lower marker lights, no top lights
- Grating: Covers top of mixed tank